

# SHARKI

## SCHEDA TECNICA

Revisione : 27/10/2022

Prodotto: **Sharki**  
Categoria: Linea Impero  
Azienda: Loggia

### General Characteristics

SHARKI is an acrylic finish for interior decoration of great charm with a satin sandblasted effect that creates an irregular texture that evokes the designs left by the wind on the sand dunes; suitable for both classic and modern environments.

### Application

SHARKI is ideal for the protection and decoration of interior walls of prestigious ancient or modern buildings, such as villas, hotels, banks and offices.

### Preparation



Before applying SHARKI it is necessary to proceed with an adequate preparation of the surface by means of smoothing powders or pastes (such as FLYSTUK); 12 hours after applying the smoothing compound, smooth the substrate with sandpaper (a P150 grain type is recommended). After sanding proceed with the elimination of dirt and dust, apply a coat of FISSACRIL acrylic fixative diluted with water in the ratio 1: 1/1: 3. 4-5 hours after applying the fixative, apply 2 coats of WHITE OR COLORED UNIVERSAL PRIMER in the same shade as the finish using a roller.

### Application Methods



Spalter 1x10cm or plafoncino 3x10cm: Product dilution: 5-10% with water.

After 6-8 hours from the application of the UNIVERSAL PRIMER proceed with the application of SHARKI by crossing the brush strokes until the wall is completed. To obtain a wall richer in shades of sand, the second coat of SHARKI can be applied filling in the most empty spaces. It is possible to have various SHARKI effects: oblique effect or simply vertical effect, spreading the product in one direction only, from top to bottom, until the wall is completed.

Application temperature:	+5 ÷ +35	°C
Relative humidity of application:	< 85%	
Recommended thickness:	50 ÷ 100	µm per coat
Dust dry:	1-2	h
Repaintable after:	6-8	h
Deep dry:	48	h
Tool cleaning:	water	

## Painting:



The product can be colored with the tinting systems of the L'ANGELO and L'ANGELO OX lines, as well as with the universal dyes available on the market.

It is advisable to mix different manufacturing batches of the same color with each other to avoid possible differences in shades during application.

SHARKI exists in the classic versions and in the GOLD, SILVER and DIAMOND version, sandblasted effect finishes with pearl silver, pearl gold or glitter finish.

Specific weight:	1,45 ÷ 1,55	Kg/l
Viscosity:	5000-10000	cPs
pH:	6-7	
Solid in weight:	60%	
Theoretical yield:	6-7	mq/l
Color:	Color folder	
Aspect:	Sandblasted gold pearl, silver pearl and diamond	
Packs:	0,75-2.5 - 4	l

## Storage:



The unopened product, stored intact in a dry and cool place, has a storage life of not less than 24 months.



After use carefully close the package and store it upside down.

Minimum storage temperature: + 5 ° C

Maximum storage temperature: + 30 ° C

## Safety Precautions:

For all information relating to the handling of the product as well as its correct disposal, please refer to the Safety Data Sheet.

## **Warnings**

---

The information contained in this sheet is provided to the best of our technical knowledge. However, these indications and suggestions cannot have the value of a guarantee for the applicator, since the conditions of use of the product are beyond our direct control. It is therefore advisable to ascertain the suitability of the product for the specific case with preliminary tests.

**Loggia Industria Vernici S.r.l.** Via Colle d'Alba di Levante – 04016 B.go S. Donato - Sabaudia (LT) –  
ITALY

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. [www.loggia.it](http://www.loggia.it), E-mail [commerciale@loggia.it](mailto:commerciale@loggia.it).

**BVQI certified company for the UNI EN ISO 9001-2000 quality system.**