

# SPECCHIO CERA

## SCHEDA TECNICA

Revisione : 13/01/2023

Prodotto: **Specchio cera**  
Categoria: Linea Impero  
Azienda: Example

### General Characteristics

SPECCHIO CERA allows to obtain exceptional results in the finishing of Venetian Stucchi and Marmorini. It gives the treated supports shine, chromatic variations, surface resistance, water repellency, inalterability over time.

### Application

Protective wax for internal use.

### Application Methods



Ready-to-use product: apply with a wide spatula.

Take a small amount of wax with a spatula and deposit it on the wide spatula, spread a thin layer of wax over the entire surface after 12 -24 hours polish with a soft cloth.

Specific weight:	1,0	Kg/l
Viscosity:	Tixotropico	cPs
Touch dry:	10	minutes
Theoretical yield:	20-25	m <sup>2</sup> /l
Polishable:	12-24	hours
Packaging:	1	1

### Storage:



The unopened product, stored intact in a dry and cool place, has a shelf life of not less than 24 months.

After us, carefully close the package and store it upside down.



Minimum storage temperature: + 5 ° C

Maximum storage temperature: + 30 ° C

## **Safety Precautions:**

---

For all information relating to the handling of the product, as well as its correct disposal, please refer to the Safety Data Sheet.

## **Warnings**

---

The information contained in this sheet is provided to the best of our technical knowledge. However, these indications and suggestions cannot have the value of a guarantee for the applicator, since the conditions of use of the product are beyond our direct control. It is therefore advisable to ascertain the suitability of the product for the specific case with preliminary tests.

**Loggia Industria Vernici S.r.l.** Via Colle d'Alba di Levante – 04016 B.go S. Donato - Sabaudia (LT) – ITALY

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. [www.loggia.it](http://www.loggia.it), E-mail [commerciale@loggia.it](mailto:commerciale@loggia.it).

**BVQI certified company for the UNI EN ISO 9001-2000 quality system.**